



HUSKEY Specialty Lubricants

manufactured by HUSK-IIT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 - Fax: (951) 340-4011
(888) 4-HUSKEY - www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 - Fax: (330) 425-9637
(800) 238-LUBE

Conforms to HCS 2012 - United States

SAFETY DATA SHEET

Section 1. Identification

Product identifier(s) : HUSKEY™ GOLD BRONZE THREAD COMPOUND

Trademark(s) used on the label

Other means of identification : Product code: 40400

Identified uses : Not available.

Manufacturer : HUSKEY Specialty Lubricants
1580 Industrial Ave.
Norco, CA 92860 USA
Tel: 1-951-340-4000
Tel: 1-888-448-7539 (Toll-free in the USA)
Fax: 1-951-340-4011

Emergency telephone number (with hours of operation) : CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3877 (24/7)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : AQUATIC HAZARD (ACUTE) - Category 1
AQUATIC HAZARD (LONG-TERM) - Category 1

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Section 2. Hazards identification

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product code : 40400

Ingredient name	%	CAS number
Zinc powder - zinc dust (stabilized)	≥5 - ≤10	7440-66-6
Copper	≥1 - ≤3	7440-50-8
Zinc oxide	≤0.3	1314-13-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.

Section 4. First aid measures

Ingestion : No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Zinc powder - zinc dust (stabilized) Copper Zinc oxide	None. ACGIH TLV (United States, 3/2016). TWA: 1 mg/m ³ , (as Cu) 8 hours. Form: Dust and mist TWA: 0.2 mg/m ³ 8 hours. Form: Fertilizer and/or industrial use. NIOSH REL (United States, 10/2013). TWA: 1 mg/m ³ , (as Cu) 10 hours. Form: Dusts and mists OSHA PEL (United States, 6/2016). TWA: 1 mg/m ³ 8 hours. Form: Dusts and mists TWA: 0.1 mg/m ³ 8 hours. Form: Fertilizer and/or industrial use. NIOSH REL (United States, 10/2013). CEIL: 15 mg/m ³ Form: Dust TWA: 5 mg/m ³ 10 hours. Form: Dust and fumes STEL: 10 mg/m ³ 15 minutes. Form: Fertilizer and/or industrial use. OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. Form: Fertilizer and/or industrial use. TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2016). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction

Section 8. Exposure controls/personal protection

STEL: 10 mg/m³ 15 minutes. Form: Respirable fraction

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Paste.
- Color** : Dark copper.
- Odor** : Petroleum
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Open cup: 221.11°C (430°F) [Cleveland.]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.

Section 9. Physical and chemical properties

- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1.31 g/ml
- Solubility** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Flow time (ISO 2431)** : Not available.

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Do not heat above flash point.
- Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials and acids.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

There is no data available.

Irritation/Corrosion

There is no data available.

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
Crystalline silica, respirable powder	-	1	Known to be a human carcinogen.

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

Section 11. Toxicological information

There is no data available.

Specific target organ toxicity (repeated exposure)

Name	Category	Target organs
Crystalline silica, respirable powder	Category 1	respiratory tract

Aspiration hazard

There is no data available.

Information on the likely routes of exposure : Ingestion.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	152644.8 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	
Zinc powder - zinc dust (stabilized)	Acute EC50 106 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours	
	Acute EC50 10000 µg/L Fresh water	Aquatic plants - Lemna minor	4 days	
	Acute IC50 65 µg/L Marine water	Algae - Nitzschia closterium - Exponential growth phase	4 days	
	Acute LC50 65 µg/L Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours	
	Acute LC50 68 µg/L Fresh water	Daphnia - Daphnia magna	48 hours	
	Acute LC50 12.21 µg/L Marine water	Fish - Periophthalmus waltoni - Adult	96 hours	
	Chronic EC10 27.3 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours	
	Chronic EC10 59.2 µg/L Fresh water	Daphnia - Daphnia magna	21 days	
	Chronic NOEC 9 mg/L Fresh water	Aquatic plants - Ceratophyllum demersum	3 days	
	Chronic NOEC 178 µg/L Marine water	Crustaceans - Palaemon elegans	21 days	
	Chronic NOEC 2.6 µg/L Fresh water	Fish - Cyprinus carpio	4 weeks	
	Copper	Acute EC50 1100 µg/L Fresh water	Aquatic plants - Lemna minor	4 days
		Acute EC50 2.1 µg/L Fresh water	Daphnia - Daphnia longispina - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
		Acute IC50 13 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
Acute IC50 5.4 mg/L Marine water		Aquatic plants - Plantae - Exponential growth phase	72 hours	
Acute LC50 0.072 µg/L Marine water		Crustaceans - Amphipoda - Adult	48 hours	
Acute LC50 7.56 µg/L Marine water		Fish - Periophthalmus waltoni - Adult	96 hours	
Chronic NOEC 2.5 µg/L Marine water		Algae - Nitzschia closterium - Exponential growth phase	72 hours	
Chronic NOEC 7 mg/L Fresh water		Aquatic plants - Ceratophyllum demersum	3 days	
Chronic NOEC 0.02 mg/L Fresh water		Crustaceans - Cambarus bartonii - Mature	21 days	
Chronic NOEC 2 µg/L Fresh water		Daphnia - Daphnia magna	21 days	
Zinc oxide	Chronic NOEC 0.8 µg/L Fresh water	Fish - Oreochromis niloticus - Juvenile (Fledgling, Hatchling, Weanling)	6 weeks	
	Acute IC50 1.85 mg/L Marine water	Algae - Skeletonema costatum	96 hours	
	Acute IC50 46 µg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours	
	Acute LC50 98 µg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours	
	Acute LC50 1.1 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours	

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Zinc oxide	-	60960	high

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Copper)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc powder - zinc dust (stabilized), Copper). Marine pollutant (Zinc powder - zinc dust (stabilized), Copper)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc powder - zinc dust (stabilized), Copper)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.

AERG : 171

DOT-RQ Details : Zinc powder - zinc dust (stabilized) 1000 lbs / 454 kg

Additional information

DOT Classification : Non-bulk packages of this product are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by inland waterway. The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg.
Reportable quantity 15782.8 lbs / 7165.4 kg [1445 gal / 5469.8 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1. 4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

This product does not dry or produce dust under normal use. Since the product is in paste/grease form, the risk of exposure to dust is minimal or non-existent and the related hazard statements are therefore not shown in this SDS even if some hazardous ingredients are listed in this Section for other regulatory requirements.

U.S. Federal regulations : **TSCA 6 proposed risk management:** Lead
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
TSCA 12(b) one-time export: None of the components are listed.
TSCA 12(b) annual export notification: None of the components are listed.
United States inventory (TSCA 8b): All components are listed or exempted.
Clean Water Act (CWA) 307: Zinc powder - zinc dust (stabilized); Zinc oxide; Lead; Cadmium; Copper

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed
Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

Name	Classification
Crystalline silica, respirable powder	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) (inhalation) - Category 1

SARA 313

	Product name	CAS number
Form R - Reporting requirements	Zinc powder - zinc dust (stabilized) Copper Lead	7440-66-6 7440-50-8 7439-92-1
Supplier notification	Zinc powder - zinc dust (stabilized) Copper	7440-66-6 7440-50-8

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Distillates (petroleum), solvent-refined heavy naphthenic; Distillates (petroleum), hydrotreated light naphthenic; Zinc powder - zinc dust (stabilized); Copper; Natural Graphite; Glass, oxide, chemicals; Diiron trioxide; Limestone; Hydrous magnesium silicate

Section 15. Regulatory information

- New York** : The following components are listed: Zinc powder - zinc dust (stabilized); Copper
- New Jersey** : The following components are listed: Distillates (petroleum), solvent-refined heavy naphthenic; Distillates (petroleum), hydrotreated light naphthenic; Zinc powder - zinc dust (stabilized); Copper; Natural Graphite; Crystalline silica, amorphous; Diiron trioxide; Crystalline silica, respirable powder; Limestone; Hydrous magnesium silicate
- Pennsylvania** : The following components are listed: Zinc powder - zinc dust (stabilized); Copper; Natural Graphite; Crystalline silica, amorphous; Diiron trioxide; Crystalline silica, respirable powder; Limestone; Hydrous magnesium silicate

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Crystalline silica, respirable powder, Copper, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Inventory list

National inventory

- Canada** : All components are listed or exempted.
- China** : All components are listed or exempted.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.

Petroleum components contained in this product meet the IP 346 criteria of less than 3 percent DMSO-extractable components.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	1
Flammability		1
Physical hazards		1

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method Calculation method

History

Date of issue mm/dd/yyyy : 06/15/2018

Date of previous issue : 06/15/2017

Version : 4

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.