

# \* PRODUCT INFORMATION \*

## **HUSKEY™ 105 HI-TEMP GREASE**

### **DESCRIPTION**

**HUSKEY 105 HI-TEMP GREASE** represents some of the latest in lubrication technology. It is formulated from the highest quality petroleum base stocks coupled with the newest additives available, to help produce the high temperature characteristics usually associated with expensive synthetic based grease.

This unique blend, together with its shear stable thickening system, provides the maximum protection against friction, wear and corrosion.

**HUSKEY 105 HI-TEMP GREASE** is not just another "no-melt" grease and does not contain any moly, graphite or clay fillers.

### **USAGE**

**HUSKEY 105 HI-TEMP GREASE** was designed primarily for severe high-temperature service but has unsurpassed performance in normal grease applications. Due to its high film strength, anti-wear properties and wide temperature range (10°F to 586°F), it may be used in a wide variety of applications which include bearings and slides in ovens, kiln cars, mills, pumps, rolls, forklifts, etc.

### **ADVANTAGES**

- High Film Strength
- Wide Temperature Range
- Extreme Pressure Resistance
- Non-melting
- Water-resistant
- Reduces Friction and Wear

### **PACKAGE AVAILABILITY**

Convenient disposable gun-loader 14 oz. Cartridges,  
1 gal. Pail, 5 gal. Pail, 15 gal. Keg, and 55 gal. Drum



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE

# \* PRODUCT INFORMATION \*

## TYPICAL PROPERTIES

**DESCRIPTION:** **HUSKEY** PRODUCT: 105 HI-TEMP GREASE  
Color: Brown  
Base Oil: Petroleum  
Thickener: Synthetic

TEST	ASTM METHOD	TYPICAL RESULTS
N.L.G.I. Grade	----	2
Worked Penetration	D-217	265-295
Pour Point, °F	D-97	10
Flash Point, °F	D-92	586
Dropping Point, °F	D-566	NONE
Base Oil Viscosity, cSt @ 40°C		473
cSt @ 100°C		31.7
Timken OK Load, lbs.	D-2509	50
Rust Test	D-1743	PASS

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

07/16



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

**Western Region Office:**  
1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

**Eastern Region Office:**  
8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE