

* PRODUCT INFORMATION *

HUSKEY™ 2000

LUBRICATING PASTE AND ANTI-SEIZE COMPOUND FOR HIGH TEMPERATURE

DESCRIPTION

HUSKEY 2000 is a heavy-duty industrial anti-seize and lubricating paste containing very finely divided metallic particles in a special no-melt semi-synthetic carrier. **HUSKEY 2000** leaves a protective film that seals and protects metal parts even under the most extreme conditions of heat, pressure, steam and saltwater exposure.

USAGE

HUSKEY 2000 was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to +2000°F.

HUSKEY 2000 was formulated to fit a wide variety of marine, metal working, automotive, oilfield, construction and farm equipment applications. A few such examples include.

- THREADED FITTINGS
- RIG DRIVES
- SPROCKETS & CHAINS
- CASTING EQUIPMENT
- SPLINES
- LOW SPEED WORM GEARS
- MANIFOLD STUDS & BOLTS
- WINCHES
- BRAKE CAMS & PINS
- CONVEYORS
- VALVE SHAFTS
- SENSORS

ADVANTAGES

HUSKEY 2000 is not just another anti-seize/thread lubricant. Unlike conventional products on the market, the maximum blend of metallic solids has been homogenized into a specially designed semi-synthetic lubricating grease which does not contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application. It also helps to reduce friction of metal surfaces and allows easy movement of threaded connections during assembly and disassembly which makes for tighter make-ups and leak free joints. Other advantages include:

- PROTECTS TO +2000 °F.
- REDUCES TORQUE
- PREVENTS CARBON FUSION
- PREVENTS RUST & CORROSION
- EXCELLENT LUBRICITY
- PREVENTS GALLING & SEIZING
- STEAM & WATER PROOF
- CHEMICAL RESISTANT
- EXTREME PRESSURE LUBRICANT
- NON-MELTING



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

DESCRIPTION

HUSKEY PRODUCT: 2000 ANTI-SEIZE
Color: Copper Gray
Base Oil: Semi-Synthetic
Thickener: Synthetic
Texture: Buttery
U.S.D.A. Rating: H-2

TESTS

ASTM TEST METHOD

RESULTS

N.L.G.I. Grade	-----	1
Penetration		
Unworked	D-217	290
Worked, 60 strokes		320
Base Oils Viscosity,	D-445	
SUS @ 100°F		4292
SUS @ 210°F		223
cSt @ 40°		796
cSt @ 100°C		46
Pour Point, °F	D-97	14
Flash Point °F	D-92	450
Dropping Point, °C (°F)	D-566	None
Copper strip corrosion	D-4048	
(24hrs. @ 210°F)		1A
Salt Spray Test	B-117	
5% Salt, 24hrs. @ 95°F		No Corrosion
Coefficient Friction (LFW-4)	-----	
Static		0.121
Dynamic		0.079
Four Ball Wear Scar, mm	D-2266	
(40Kg, 1 hr @ 1200 rpm)		0.92

PACKAGE AVAILABILITY

3 gram Lube-Paks® (packed 1000 per case),
½ pint brush top jar (packed 12 to a case), 1 pint brush top jar (packed 12 to a case),
1-gal. Pail, 5 gal. Pail, 15 gal. Keg and 55 gal. Drum

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 8/14



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE