

* PRODUCT INFORMATION *

HUSKEY™ API SPECIAL **HIGH PRESSURE THREAD SEALING COMPOUND**

DESCRIPTION

HUSKEY API SPECIAL is a high pressure thread sealing compound that represents the industry standard for tubing and casing in deep, high pressure wells due to its high percentage (64%) of lubricating solids. This product is adapted from the API Bulletin 5A2.

USAGE

HUSKEY API SPECIAL is highly recommended as a high pressure thread sealant for all fine threaded down hole connections, operating in pressures of up to 10,000 p.s.i.

ADVANTAGES

HUSKEY API SPECIAL provides maximum protection to threaded connections against leakage, galling, seizing and other thread hazards.

SERVICE RATING

0EF(-18EC) to 500□F (260□F)

OPERATING RANGE

Base grease provides lubrication to 400EF (204EC). Metallic and lubricating solids provide lubrication to 1900EF (1038EC).

TYPICAL SPECIFICATIONS

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULT</u>
Drop Point, EF Min.	D-566	280
Flash Point, EF	D-92	430
Pour Point, EF	D-97	0
Brushability (minimum)EF	----	15

PACKAGE AVAILABILITY

1-gal. Pail, 3-1/2 Gal Pail, and 5-gal. Pail

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

8/98



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE