

* PRODUCT INFORMATION *

HUSKEY™ DYNA-MITE RED GREASE

DESCRIPTION

HUSKEY DYNA-MITE RED GREASE is a unique high-temperature, extreme pressure, non-melting premium quality grease designed for very heavy-duty service in adverse environments. It is a blend of high quality petroleum oil and special synthetic polymers which work together to form an extremely water-resistant, tough lubricating film that prevents water washout and metal-to-metal contact even under extreme pressure or shock loading. **HUSKEY DYNA-MITE RED GREASE** is formulated with the optimum amounts of additives to provide maximum protection against rust, corrosion and oxidation. **HUSKEY DYNA-MITE RED GREASE** contains no fillers or clay thickeners. The distinctive red color makes it easy to identify during and after lubrication.

USAGE

HUSKEY DYNA-MITE RED GREASE with its unique qualities can be used in a wide variety of applications, thus reducing the number of lubricants you must keep on hand. Some such applications include ball and roller bearings, bushings, slides, valve operators and bearings, gears, screw drives, couplings, cranes and general lubrication, especially where loads may be quite heavy and speeds slow.

ADVANTAGES

- Withstands Extreme Pressures
- Wide Temperature Range (10°F to 525°F)
- Extremely resistant to Water Washout
- Excellent Metal Adherence
- Will Not Melt or Run Out
- Prevents Rust and Corrosion
- Reduces Wear

PACKAGE AVAILABILITY

Convenient disposable gun-loader 14oz. Cartridges,
1-gal. Pails, 5-gal. Pails, 15-gal. Kegs,
and 55-gal. Drums



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

DESCRIPTION	HUSKEY Product:	DYNA-MITE RED GREASE
	Color:	Red
	Base Oil:	Semi-Synthetic
	Thickener:	Synthetic
	Texture:	Buttery

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULTS</u>
N.L.G.I. Grade	----	2
Worked Penetration	D-217	
60 Strokes		275
10,000 Strokes		290
Base Oil Viscosity,	D-445	
SUS @ 100°F		3650
SUS @ 210°F		200
cSt @ 40°C		677
cSt @ 100°C		40
Pour Point, °F	D-97	10
Flash Point, °F	D-92	525
Dropping Point, °F	D-566	NONE
Corrosion Preventative Test	D-1743	PASS
Timken OK Load, lbs.	D-2509	60

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 5/18



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE