

* PRODUCT INFORMATION *

HUSKEY™ MOLYPLEX GREASE

DESCRIPTION

HUSKEY MOLYPLEX GREASE is a premium quality, multi-purpose grease containing a blend of molybdenum disulfide (Moly) and special lubricating solids. This unique combination of solid lubricants offers superior performance compared with pure molybdenum disulfide greases. This optimum percentage of lubricating solids is homogenized into a blend of the finest quality base oils and thickeners available. Treated with the most modern additives to provide lasting protection against water, extreme pressure, temperature, fretting and oscillating conditions.

USAGE

HUSKEY MOLYPLEX GREASE is a truly multi-service grease. Because of its wide temperature range (10°F to 465°F) and excellent film strength, it may be utilized not only where a general purpose grease is employed but where adverse conditions are found. Some typical applications include all types of ball and roller bearings, cams, splines and sliding surfaces which may be subject to severe impact loads or exposed to extreme atmospheric conditions. **HUSKEY MOLYPLEX GREASE** meets CATERPILLAR® MPMG specification.

ADVANTAGES

PLATING ACTION — **HUSKEY MOLYPLEX** is fortified with sub-micron size lubricating solids which impregnates the metal surfaces, improving metal finish and developing a smoother surface, thus reducing friction and wear.

NON-MELTING — **HUSKEY MOLYPLEX** is formulated to not melt or run out of the bearing or metal surfaces even under extreme temperatures. (Contains no clay fillers.)

BETTER PROTECTION — **HUSKEY MOLYPLEX** is engineered to provide excellent protection against wear, rust, oxidation and corrosion, thus extending equipment life and reducing maintenance cost.

PACKAGE AVAILABILITY

Convenient disposable gun loader 14 oz. Cartridges,
1-gal. Pail, 5-gal. Pail, 15-gal. Keg and 55-gal Drum



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

DESCRIPTION	HUSKEY Product:	MOLYPLEX GREASE
	Color:	Moly Grey
	Base Oil:	Semi-Synthetic
	Thickener:	Synthetic
	Texture:	Buttery
	Solid Lubricant:	Molybdenum Disulfide

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULTS</u>
N.L.G.I. Grade	----	2
Worked Penetration, 60 Strokes	D-217	275
10,000 Strokes		290
Base Oil Viscosity, cSt @ 40°C	D-445	685
cSt @ 100°C		45
Pour Point, °F	D-97	10
Flash Point, °F	D-92	465
Dropping Point, °F	D-566	NONE
Corrosive Preventative Test	D-1743	PASS
Timken OK Load, lbs.	D-2509	55

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

07/16



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE