

* PRODUCT INFORMATION *

HUSKEY™ NO. 3 **GENERAL PURPOSE** **VALVE LUBRICANT & SEALANT**

DESCRIPTION

HUSKEY No. 3 VALVE LUBRICANT is a totally synthetic valve lubricant and sealant that contains no graphite, molybdenum disulfide, or other fillers. The broad temperature range and multi-service applications have found wide acceptance in the petrochemical industry.

USAGE

HUSKEY No. 3 is designed for use in all lubricated valves in hydrocarbon, L.P.G., aromatics, natural gas, aqueous solutions, water, acids, caustics and many other services.

ADVANTAGES

- Broad Serviceability Range
- 100% Synthetic, contains no soaps or clays
- Will not dry out or harden in valve
- Economical, does the work of several valve lubricants

TYPICAL SPECIFICATIONS

Color	Amber
Texture	Tenacious and Smooth
Service Temperature	30EF to 500EF
Dropping Point	None
Base Oils and Thickener	Synthetic
Special Additive	Sub-Micron PTFE

PACKAGE AVAILABILITY

5 qt. Cans, 5 gal. Pails, and 15 gal. Kegs
J & K gun size Sticks
Small Sticks for screw type lubricators

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

2/98



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE