

# \* PRODUCT INFORMATION \*

## **HUSKEY™ No. 6** **GATE VALVE LUBRICANT/SEALANT** **FOR WKM AND OTHER VALVES WITH BODY CAVITIES**

### **DESCRIPTION**

**HUSKEY No. 6** is a blend of synthetic fluids and thickeners designed to impart excellent corrosion protection, lubricity and superior sealing qualities for all major body fill type valves.

### **USAGE**

**HUSKEY No. 6** is formulated to give superior service in oil production, dilute alkalies, dilute acids, salt water mixtures and general water service.

### **ADVANTAGES**

- 100% Synthetic Will Not Wash Out
- Non-Toxic
- Non-Soap Thickener
- Excellent Sealing Ability
- Economical

### **TYPICAL SPECIFICATIONS**

Color	Amber
Texture	Smooth & Tenacious
Service Temperature	20°F to 545°F
Base Oil	Synthetic

### **PACKAGE AVAILABILITY**

5 qt. Can, 5 gal. Pail, and 15 gal. Keg

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the product for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 10/09



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE