

* PRODUCT INFORMATION *

HUSKEY™ RB-2 **ALL PURPOSE DRILL COLLAR &** **TOOL JOINT ANTI-SEIZE COMPOUND**

DESCRIPTION

HUSKEY RB-2 is one of our most versatile anti-seize and thread sealing compounds. It consists of a balanced blend of pure metallic zinc, amorphous graphite and other lubricating solids homogenized into a high temperature grease base. **HUSKEY RB-2** is fortified with the most modern additives to maximize protection against rust, corrosion and water washout.

USAGE

Due to its versatility, **HUSKEY RB-2** is used extensively in the industry, both as an anti-seize compound for drill collars and tool joints and as a sealing compound for casing and tubing. It is also used extensively in steam injection wells due to its resistance to high temperatures.

ADVANTAGES

HUSKEY RB-2 will prevent seizure, galling, bellling of tool joints, etc., on rotary-shouldered connections. It provides sealing protection and prevents leakage even in high-pressure, deep wells. **HUSKEY RB-2** provides excellent shoulder-to-shoulder make-up in high angle drilling.

SERVICE RATING

0EF(-18EC) to 1000EF (537EC)

OPERATING RANGE

Base Grease provides lubrication to 450EF (232EC). Lubricating and metallic solids provide lubrication to 1900EF (1037EC)

TYPICAL SPECIFICATIONS

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULTS</u>
Base Thickener	-----	Synthetic
Base Oil Viscosity	-----	
SUS @ 100EF	D-445	994
SUS @ 210EF	D-445	66
Worked Penetration	D-217	290-310
Drop Point, EF(ASTM D-566)	D-566	None
Flash Point, EF(ASTM D-92)	D-92	450
Pour Point,EF (ASTM D-97)	D-97	0
Brushability (minimum).EF	-----	15

PACKAGE AVAILABILITY

3 1/2 gal. Pails, and 5 gal. Pails

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. the final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

6/97



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE