

* PRODUCT INFORMATION *

HUSKEY™ RB-3 **HIGH TEMPERATURE THREAD LUBRICANT**

DESCRIPTION

HUSKEY RB-3 consists of non-volatile, high temperature grease, blended with generous amounts of powdered zinc, amorphous graphite, corrosion and oxidation inhibitors.

HUSKEY RB-3 was designed for Geothermal applications where Heat is the prime concern. **RB-3** is very effective in rock with stratified formation. Typically used with pipe sizes 3.5"-4.5" diameter, however, with extreme heat it is excellent on all pipe sizes. When dealing with heat, **HUSKEY RB-3** is definitely the professional's choice.

SERVICE RATING

0EF (-18EC) to 1200EF (649EC)

OPERATING RANGE

Base grease provides lubrication to 450EF (232EC). Lubricating solids lubricate to 1500EF (816EC).

TYPICAL SPECIFICATIONS

<u>TEST</u>	<u>ASTM METHOD</u>	<u>RESULT</u>
Base Thickener	----	Synthetic
Base Oil Viscosity, SUS @ 100EF	D-445	994
SUS @ 210EF	D-445	66
Worked Penetration	D-217	290-310
Drop Point, EF	D-566	None
Flash Point, EF	D-92	430
Pour Point, EF	D-97	0
Brushability (Minimum), EF	----	15

PACKAGE AVAILABILITY

3½ gal. Pail and 5 gal. Pail

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

5/98



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE