

* PRODUCT INFORMATION *

HUSKEY™ RUST RELEASE

DESCRIPTION

HUSKEY RUST RELEASE is a unique blend of a specially formulated synthetic wax and the finest quality lubricating fluids available. Designed to produce the optimum properties of penetration, anti-corrosion, and anti-wear, **HUSKEY RUST RELEASE** penetrates deep into corroded or rusted areas breaking up corrosion and coating all surfaces to ease breakout of frozen parts. This coating protects all surfaces from further corrosion plus provides extremely long-lasting lubrication to bearings, slides and all metal surfaces.

USAGE

HUSKEY RUST RELEASE lubricating penetrating properties allow for a variety of applications which include both penetrating rusted and frozen parts and general lubricating such as:

- Rusted and seized bolts and parts
- Rusted couplings, bearings, pivot and guide pins
- Squeaking springs, chains, and hinges
- Electric motor brushes or couplers
- Tie downs on auto transporters
- Lubricates & protects firearms
- Lubricating sticking locks, hinges, cranks, windows, sliding doors
- Lubricating on conveyors, chain drives, material handling equipment
- Lubricating on cables, farm machinery, construction equipment, draglines

ADVANTAGES

- Penetrates Fast
- Rust and corrosion protection
- Synthetic wax film protective coating and lubricant
- Eases break-out
- Reduces down time
- Displaces Moisture

CAUTION: Contains solvents which may affect certain plastics and rubbers; test thoroughly before use.

PACKAGE AVAILABILITY

16 fl. oz. (11 oz. net) Aerosol Cans (12 cans per case)
1 gal. Jug (4/case), 5 gal. Pail, 15 gal. Keg, 55 gal. Drum



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE

* PRODUCT INFORMATION *

TYPICAL PROPERTIES

<u>DESCRIPTIONS</u>	<i>HUSKEY</i> PRODUCT:	RUST RELEASE
	Color:	Light Amber
	Physical Form,	
	As Supplied:	Low Viscosity Liquid
	Without Solvent Carrier:	Thin Semi-Solid Film

<u>TEST</u>	<u>ASTM TEST METHOD</u>	<u>RESULTS</u>
Base Carrier	-----	Petroleum Solvent
Flash Point, °F	D-92	230 (non-aerosol)
Coefficient of Friction	LFW-4	
Dynamic		0.090
Static		0.116
Falex Pin & Vee Block ft. lb., Pass	D-3233 (B)	1000
Salt Spray Corrosion (5% @ 100 hrs.)	B-117	No Rust
Humidity Cabinet Test (100 hrs. @ 120°F)	D-1748	Pass

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

06/14



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:
1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:
8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE