

* PRODUCT INFORMATION *

HUSKEY™ SGL-800 SERIES OILS

DESCRIPTION

HUSKEY SGL-800 SERIES OILS are heavy duty extreme pressure oils formulated from the highest quality selected synthetic base oils and additives available. **HUSKEY SGL-800 SERIES OILS** have been compounded to be more reliable, even under the toughest conditions. These high quality 100% synthetic oils have been designed to give extra protection in high and low temperature applications. **HUSKEY SGL-800 SERIES OILS** are NSF H-2 Registered for use in food processing plants.

USAGE

HUSKEY SGL-800 SERIES OILS were formulated primarily for heavy-duty industrial enclosed gear sets and heavily loaded plain and roller bearings. Due to their outstanding high temperature and low carbon forming characteristics they are in excellent choice for high temperature chains and bearings found in lithograph ovens, dryers, kilns and stenter frames, etc.

ADVANTAGES

- Wide Temperature Range.
- Excellent Load-Carrying Capacity.
- Reduces Wear and Protects Against Scuffing.
- Protects Against Rust, Corrosion, and Foaming.
- Increased Parts Life.
- Extended Drain Intervals.
- Reduced Maintenance and Down Time.
- NSF H-2 Registered (No. 138198)

TEST

ASTM METHOD

TYPICAL PROPERTIES

ISO GRADE

		<u>68</u>	<u>100</u>	<u>150</u>	<u>220</u>	<u>320</u>	<u>460</u>
Color	----	Amber	Amber	Amber	Amber	Amber	Amber
Viscosity, cSt @ 40°C	D-445	68	100	150	220	320	460
Viscosity, cSt @ 100°C	D-445	4.7	14.5	19.4	29.8	34.9	53.9
Viscosity Index, Min.	----	128	134	142	144	150	156
Flash Point, °F	D-92	500	510	514	515	520	530
Pour Point, °F	D-97	-63	-53	-46	-42	-37	-29
Corrosion Preventative Test	D-665	Pass	Pass	Pass	Pass	Pass	Pass
4-Ball Wear Scar (40 Kg, 167 °F, 1 hr, 1200 rpm)	D-4172	0.51	0.52	0.51	0.49	0.45	0.46
Conradson Carbon, %	D-189	0.01	0.01	0.01	0.015	0.015	0.015



PACKAGE AVAILABILITY

1-gal. Jugs (4/case), 5-gal. Pails, 15-gal. Kegs and 55-gal. Drums

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation. 07/16



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE